



Typical Properties Sheet

11/8/2018

Product: **20PPI**

| <u>Physical Property</u> | <u>Value</u> | <u>Test Method</u> |
|---------------------------------------|---------------|--------------------|
| Color | Charcoal Grey | |
| Density (lbs / ft ³) | 1.15 - 1.50 | ASTM D-3574-01 |
| Compression Deflection @ 25% (psi) | 0.25 min | ASTM D-3574-01 |
| Tensile Strength (psi) | 10 min | ASTM D-3574-01 |
| Elongation (%) | 130 min | ASTM D-3574-01 |
| Tear Strength (lbs / lin inch) | 2.0 min | ASTM D-3574-01 |
| Flame Resistance | N/A | |
| Pore Size (ppi) | 15 - 25 | Visual Call |

This foam is an ester

This information is based on actual testing in a controlled environment. However, as conditions of use are not within our control, Amcon does not guarantee from use of such products or other information herein; no warranty expressed or implied is given. It is the user's responsibility to determine the appropriateness of the products for their specific end uses.

WARNING: URETHANE FOAM IS FLAMMABLE!

**Urethane Foam should not be exposed to open flame or other ignition sources.
Urethanes burn rapidly with great heat and release gases which are extremely hazardous.**

5360 Main St. NE Minneapolis, MN 55421

Ph. 888-360-8050

www.amconfoam.com